



Paris Grey



Paris Rust



Paris Camel



Paris Sand

Paris


This fabric is a flat weave with a combination of natural and synthetic yarns.

Care kit: Cleaning glove dry from LCK

composition	width	lightfastness	abrasion
58%CO,23%CV,19%JU	app. 140 cm	ISO 4	app. 20.000 Martindale



Amsterdam Black



Amsterdam Rust



Amsterdam Sand

Amsterdam


This fabric is a combination flat weave of natural yarns.

Care kit: Complete care kit & strong cleaner from Puratex

composition	width	lightfastness	abrasion
60%LI,38%WO,2%PES	app. 130 cm	ISO 5	app. 30.000 Martindale



Antwerp Grafite



Antwerp Ash



Antwerp Beige




Antwerp Sand

Antwerp


This fabric is a flat weave with a combination of natural yarns.

Care kit: Cleaning glove dry from LCK


composition	width	lightfastness	abrasion
68%LI,14%JU,10%CV,8%CO	app. 140 cm	ISO 4	app. 20.000 Martindale




Stockholm Black



Stockholm Rust



Stockholm Nude



Stockholm Silver

Stockholm

This fabric is a chenille.

Care kit: Cleaning glove dry from LCK

composition	width	lightfastness	abrasion
39%LI,27%JU,24%CV,10%CO	app. 140 cm	ISO 4-5	app. 30.000 Martindale



Riga Blue




Riga Olive




Riga Grey



Riga Beige



Riga Mouse



Riga Sand

Riga


This fabric has a natural look and is a flat weave of natural yarns.

Care kit: Cleaning glove dry from LCK


composition	width	lightfastness	abrasion
60%CO,40%JU	app. 140 cm	ISO 4-5	app. 24.000 Martindale



Porto Olive



Porto Grey



Porto Ash



Porto Silver



Porto Sand

FABRIC DESCRIPTION

Information

Flat woven fabrics are woven fabrics in which 2 yarn groups are at right angles to each other. The closer the yarns are to each other, the higher the density, the heavier the fabric. In addition, the thickness of the yarns is also important in terms of the construction and weight of the fabric.

Features


Modern and fresh color palette.
Suitable for both tight and loose upholstery.

Maintenance


We recommend: Complete care set & strong cleaner from Puratex

Additional information

composition	width	lightfastness	abrasion
38% CO,31% AC,14% PL,9% LI,8% VI	app. 138 cm	ISO 4-5	app. 29.000 Martindale




Odense Grafite




Odense Taupe



Odense Grey



Odense Blue



Odense Olive



Odense Sand

FABRIC DESCRIPTION

Information

Flat woven fabrics are woven fabrics in which 2 yarn groups are at right angles to each other. The closer the yarns are to each other, the higher the density, the heavier the fabric. In addition, the thickness of the yarns is also important in terms of the construction and weight of the fabric.

Features

Modern and fresh color palette.
 Woolly and soft grip.
 Suitable for both tight and loose upholstery.
 Fabrics with wool may be more likely to pile.
 Use a lint comb or electric pilling device to remove these fibers.

Maintenance

We recommend: Complete care set from Puratex

Additional information

composition	width	lightfastness	abrasion
50% WO,30% LI,20% PA	app. 148 cm	ISO 4-5	app. 100.000 Martindale


Fire Safety Regulations BS5852

Test specifications


Yarn Paint

Fire retardant


Match test BS 5852 (1979)




Trier Taupe



Trier Beige



Trier Ocean



Trier Grey



Trier Sand

FABRIC DESCRIPTION

Information

Flat woven fabrics are woven fabrics in which 2 yarn groups are at right angles to each other. The closer the yarns are to each other, the higher the density, the heavier the fabric. In addition, the thickness of the yarns is also important in terms of the construction and weight of the fabric.

Features

Woolly and full grip.
 Natural and light multi-colored aspect.
 Combination of natural and synthetic yarns.
 Suitable for both tight and loose upholstery.
 Combination possible with Dixon.

Maintenance


We recommend: Complete care set & strong cleaner from Puratex

Additional information


composition	width	lightfastness	abrasion
72% PES,28% VI	app. 138 cm	ISO 5	app. 90.000 Martindale

Test specifications

Yarn Paint
 Fire retardant



Archi Lead



Archi Slate



Archi Frame

FABRIC DESCRIPTION

Information

Suitable for indoor and outdoor use.

Maintenance

Brush off loose dirt.

Spray on a cleaning solution of water and mild soap.

Use a soft brush to clean.

Allow the cleaning solution to soak into the fabric.

Rinse thoroughly until all soap residue is removed.

Allow to air dry.

We recommend the following products:

- Complete care set from Puratex
- Synthetic cleaner from Puratex

Additional information

composition	width	lightfastness
99% Sunbrella® Acrylic, 1% PES	app. 140 cm	ISO 4-5
Water-repellent & Stain-proof		



Melbourne Brown



Melbourne Grind



Melbourne Sand

FABRIC DESCRIPTION

Information

This fabric belongs to the Jess fabrics collection and is suitable for both indoor and outdoor use.

Maintenance

Be sure to wipe down the furniture regularly with a cloth or soft brush. The fabric has a special protective layer which makes it difficult for fungi and bacteria to attach themselves. The fabric is water permeable.

We recommend the following products:

- Complete care set of Puratex
- Synthetic cleaner from Puratex

Additional information

composition	width	lightfastness	abrasion
100% PP	app. 155 cm	ISO 7	app. 30.000 Martindale
Water-repellent & Stain-proof			

Maintenance kit

PURATEX



PRODUCT INFO

Description

Puratex is a care kit for furniture with fabric upholstery.

Instructions for use

Vacuum your sofa with the soft and clean furniture attachment. Pull the cleaning glove over your hand, moisten it with the distilled water and rub it over your sofa. This removes most everyday dirt. We recommend doing this on a weekly basis. Never use tap water, this is to avoid limescale. The glove is washable at 60 degrees. Protection spray: In order to effectively protect the upholstery from stains and dirt, we recommend impregnating your sofa every six months. impregnate your sofa every six months. Shake the bottle well before use. Spray the impregnation thinly and regularly. Keep the bottle upright as possible and avoid loose drops of impregnation on the fabric. Then let it dry well. The impregnation is optimal after 24 hours. Put the stain remover (Strong Cleaner) on the cloth and work on the stain with it. Always work from the outside in. Do not brush only on the stain, always clean a complete surface. Clean with distilled water and the cleaning glove. the cleaning glove. Clean the entire premises from seam to seam. Finally, re-impregnate the cleaned property.

Additional information

The care set includes

Distilled water.
Impregnating agent.
Intensive cleanser.
Cleaning glove and cloth.

General advice

Maintain your seating furniture regularly. Protect it from direct sunlight and avoid air that is too dry. Remove stains immediately.

